



Cost effective quality loudspeakers have become more and more important in the contractor market. The SDX8 loudspeakers perfectly match this criterion. Its familiar design is in perfect harmony with the transparent, yet powerfull sound exhibited. The well engineered woofer coupled with an optimised bass-reflex housing results in a high performance sound not normally associated with a relatively small cabinet.

The SDX8 loudspeakers are available in 2 different colours.

The loudspeaker is equipped with a sturdy U-bracket. As the SDX8T has the 1 step protection system build-in, the loudspeaker is protected from overloads. This all makes the SDX8 loudspeaker suited for dispersion of ambient music.

TECHNICAL SPECIFICATIONS

Type	2-way HiFi Pro, bass-reflex
Cabinet	Enforced poly plastic
Woofer	8" CP type
Tweeter	1.2" HD silk dome neodymium
Impedance	8 Ohm
RMS Power 8 Ohm	
AES Rated	140 watt
Music - Program	180 watt
Dynamic Peak (lo-cut)	380 watt
Protection system	Auto-Reset 1 Guard
SPL 1 watt/1 m	94 dB
SPL Max peak	120 dB
Frequency Range	45 Hz - 20 kHz
Speaker connectors	Push terminals
Dispersion	120° H x 100° V
IP rating	42
Dimensions (H x W x D)	375 x 280 x 240 mm
Weight	4.87 Kg